



PUF/PIR Insulated Roof & Wall Panels



PUF INSULATED SHEETS

PUF Insulated Roofing

An attractive solution to every day requirement of insulated Roofing panels. If you're looking for increased energy efficiency with reduced life cycle costs, Urban Roofs - Roof/Wallpanels solution is the answer



Features

- Excellent insulation reduces Heat and Noise considerably.
- Great Load Bearing Capacity – Purlin support need only maximum 2500mm spacing.
- Excellent Corrosion Resistance – As the sheets come with Pre-Painted Galvalume Sheet [AZ150].
- B2 Grade Fire rated PIR Roof/Wall Panels.
- Improves Energy efficiency saving heating and cooling costs.
- No Air bubbles in panels as they are manufactured in Automatic Production Line.

Specifications

Panel Thickness:

30 mm core with 38 mm crust
50 mm core with 38 mm crust

External Sheet

Lamination Thickness:

0.4 mm– Outside - PPGL 340 mpa, AZ150. Make: JSW

Color options: RAL 9002 Off White RAL 5012 Blue RAL 3016 Red

Internal Sheet

Lamination Thickness:

0.35 mm – Inside -PCGI 240 mpa, 120 gsm. Make: JSW

Color options: RAL 9002 Off White

Available Sizes

12 feet: [3660mm]
14 feet: [4268mm]
16 feet: [4880mm]
18 feet: [5487mm]
20 feet: [6100mm]
22 feet: [6707mm]
24 feet: [7317mm]

Odd Sizes against Order

Puf Details

Thickness of Puf: 30mm / 50mm

Thickness Options: 50/80/100/150mm

Density of Puf: 40kg/m³ (+/- 2kg)

+ 91 99005 55220
+ 91 94483 89842
+ 91 77608 24249
+ 91 8338 221442
+ 91 8338 220234
+ 91 8338 200442



urbanroofs.in@gmail.com



www.urbanroofs.in




**Near Mahadik Petrol Pump, Bagewadi Compound,
123/1-A, NH 4, Shirol (P) Kolhapur - 416122**

Office: Plot No. 1, S.No. 169 (B+C), Opp Somnath Mandir,
Sai-Shankar Nagar, Akkol Road, Nipani - 591237

Factory: Plot No. 3, Nipani Co-Op Industrial Estate,
Shripewadi – Jatrat Road, Nipani – 591237

PUF Insulated Wall / Ceiling Panels


PUF insulated panels are much superior alternative for conventional insulated ceiling and false ceilings. It's a pre-finished ceiling with ideal heat and thermal properties. PUF Ceiling Panel reduces radiant heat transfer and enhance comfort level.



Features

- Quick & Easy to install
- Excellent insulation drastically reduces radiant heat transfer
- Easily Customizable as per customer requirements
- Smooth Finish & Light Weight
- Zero Ozone Depletion Potential
- Aesthetically Appealing

Specifications



Panel Thickness: 30mm

External Sheet

Lamination Thickness:
0.4 mm – Outside - Make: JSW

Color options: RAL 9002
Off White

Internal Sheet

Lamination Thickness:
0.35 mm – Inside - Make: JSW

Color options: RAL 9002
Off White

Available Sizes

8 feet: [2440 mm]
10 feet: [3050 mm]

Puf Details

Thickness of Puf : 30mm
Density of Puf : 40kg/m³ (+/- 2kg)

Panel Details

Overall Width: 1032 mm
Covered Width: 1000 mm

Accessories

1. Suspension T Section: Length - 3m
2. C/L/U Section Flashing: Length - 3m
3. LI Section Inside Flashing: Length - 3m
4. Suspension Kit – It consists bottom clipping member and gripe hanger

PUF Insulated Wall and Partition Panels

Insulated panels are much superior alternative for conventional insulated walling and partition.


It's a pre-finished building panel with ideal heat and thermal properties. PUF Insulated Wall Panels reduces radiant heat transfer and enhance comfort level.

Features

- Quick & Easy to install
- Excellent insulation drastically reduces radiant heat transfer
- Easily Customizable as per customer requirements
- Smooth Finish & Light Weight
- Zero Ozone Depletion Potential
- Aesthetically Appealing



Specifications



Panel Thickness:

30mm/50mm

External Sheet

Lamination Thickness:

0.4mm/0.45mm – Outside - Make: JSW

Color options: RAL 9002
Off White

Internal Sheet

Lamination Thickness:

0.35mm/0.45mm – Inside - Make: JSW

Color options: RAL 9002
Off White

Available Sizes

30mm - 8 feet: [2440 mm]

30mm - 10 feet: [3050 mm]

50mm - 12 feet: [3660mm]

50mm - 16 feet: [4880 mm]

50mm - 20 feet: [6100 mm]

Puf Details

Thickness of Puf : 30mm & 50mm

Density of Puf : 40kg/m³ (+/- 2kg)

Panel Details

Overall Width: 1032 mm

Covered Width: 1000 mm



+ 91 99005 55220 / + 91 94483 89842 / + 91 77608 24249
+ 91 8338 221442 / + 91 8338 220234 / + 91 8338 200442



urbanroofs.in@gmail.com



www.urbanroofs.in



**Near Mahadik Petrol Pump, Bagewadi Compound,
123/1-A, NH 4, Shirol (P) Kolhapur - 416122**

Office: Plot No. 1, S.No. 169 (B+C), Opp Somnath Mandir,
Sai-Shankar Nagar, Akkol Road, Nipani - 591237

Factory: Plot No. 3, Nipani Co-Op Industrial Estate,
Shripewadi – Jatrat Road, Nipani – 591237